



It can be positioned every 30 °

**CAT6A Class Ea RJ45 plug to be assembled in the field**

- FTP TYPE: 1 piece Design
- Easy Assembly - easily terminated in the field in 2 minute without any special tools
- Wire Connection: Stranded wire AWG 27/7 to 22/7, wire diameter from 0.46 to 0.76 mm
- Wire Connection: Solid wire AWG 26/1 to 22/1, wire diameter from 0.4 to 0.64 mm
- Transmission Characteristics: CAT6A per ISO/IEC 11801 Ed.2.2:2011-06
- Compliance with class Ea to ISO/EIC 11801 Ed.2.2.2011-06, DIN EN 50173-1:2011-09 10 GB it Suitable according to IEEE 802.3an
- Suitable for Power over Ethernet(PoE, PoE plus, and UPoE)
- Cable Jacket Diameter from 6 to 9.0 mm
- Adjustable Strain Relief (6mm to 9.0mm Cable OD)
- Load Bar for Faster and Easier Wire Pattern Termination
- Reconnectable

TITLE:			 <b>Shenzhen Copperled Technology Co.,Ltd</b>	
	INCH	MM		
.X	.015	.30		
.XX	.010	.10	TITLE: CAT6A PLUG	
.XXX	.005	.05		
DRAWN BY	MA		P/N: CL-IPF-C6A02	
CHECK BY	SCALE	1:1	  REV	
	UNIT	MM		
APPD BY	SHEET	1/1	DWG NO:	
	DATE	2023/04/11		