



NOTES:

ELECTRICAL:

- 1. CONTACT RESISTANCE : 20M OHMS MAX
- 2. INSULATION RESISTANCE : 500M OHMS MIN @ 500V DC
- 3. WITHSTAND VOLTAGE : DC1000V AC700V RMS 60Hz, 1MIN
- 4. CAT. 6A PERMANENT LINK : CONFORM TO ANSI/TIA/EIA 568B. 2-10

ENVIRONMENTAL:

- 1. STORAGE : -40° TO+70°
- 2. OPERATION : -10° TO+60°

MECHANICAL

- 1. SHIELD MATERIAL: ZINC ALLOY
- 2. IDC MATERIAL: PC UL94V0 TERMINAL:PHOSPHOR BRONZE, TIN PLATING
- 3. RJ45 CONTACT LIFE: 750 TIMES MIN
- 4. IDN LIFE : 250 TIMES MIN
- 5. RJ45 DIMENSION:11.9MM*9.8MM
- 6. WEIGHT: 34.7G

TYPE

- 1. SHIELDED CAT. 6A KEYSTONE JACK
- 2. COLOUR: SILVERY WHITE

RoHS COMPLIANT

PACKING: 1pcs/PE bag+1able, 25pcs/box+1able, 250pcs/carton

MATERIAL LIST:

⑦	MODULAR COVER	FIREPROOF PC UL94V0	1	
⑥	RJ 45 JACK INSERT	8P8C 3U" GOLD PLATED	8	
⑤	PCB	1.6mm UL 94V0	1	
④	IDC BODY	FIREPROOF/PC UL 94V0	1	
③	IDC PIN	PHOSPHOR BRONZE & TINNED	8	
②	LABEL COLOR CODE	T568A/B	2	
①	IDC TERMINAL	FOR 22-26AWG CABLE	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

NEW			2013-08-28	A
DATE	REV.	CHENHUAN	CHENHUAN	2013-08-28

CUSTOMER	WG	ITEM NO.	NK4001	
PRODUCT NAME	10GB5TP KEYSTONE JACK	UNO ITEM NO.	227222	UNIT MM
DRAWNBY	CHECKBY	APPOBY	DATE	
CHENHUAN	CHENHUAN		2013-08-28	