



NOTES:

ELECTRICAL:

- 1. CONTACT RESISTANCE : 20M OHMS MAX
- 2. INSULATION RESISTANCE : 500M OHMS MIN @ 500V DC
- 3. WITHSTAND VOLTAGE : DC1000V AC700V RMS 60Hz, 1MIN
- 4. CAT. 6A PERMANENT LINK : CONFORM TO ANSI/TIA/EIA 568B. 2-10

ENVIRONMENTAL:

- 1. STORAGE : -40° TO+70°
- 2. OPERATION : -10° TO+60°

MECHANICAL

- 1. SHIELD MATERIAL: copper with nickel plated
- 2. PC UL94V0 TERMINAL: PHOSPHOR BRONZE, TIN PLATING
- 3. RJ45 CONTACT LIFE: 750 TIMES MIN
- 4. IDN LIFE : 250 TIMES MIN
- 5. RJ45 DIMENSION: 11.9MM*9.8MM

TYPE

- 1. SHIELDED CAT.6A inline coupler
- 2. COLOUR: SILVERY WHITE

RoHS COMPLIANT

PACKING: 1pcs/PE bag+lable, 100 pcs/box+lable, 500 pcs/carton

MATERIAL LIST:

③	MODULAR COVER	FIREPROOF PC UL94V0	1	
②	RJ 45 JACK INSERT	8P8C 3U" GOLD PLATED	8	
①	PCB	1.6mm UL 94V0	1	

NO.	PARTS NAME	SPECIFICATION STANDARD	QT'Y	REMARK
		NEW	2017-11-1	A
BY	CHK		DATE	REV.

CUSTOMER		ITEM NO.		396款屏蔽CAT6A	
PRODUCT NAME	UNO ITEM NO.	UNIT			
DRAWNBY	CHECKBY	APPOBY	DATE		