



COVER

- Material:**
- 1.RJ45 Housing:PC
 - 2.Phosphor Bronze with 50-60 micro-inch Nickel plated.
 - 3.Contact area: 3-50 micro-inch Gold plated
 - 4.IDC Housing: PC
 - 5.IDC Terminal material & finished:
 - 5-1:phosphor Bronze with 50 micro-inch Tin-Lead plated. Over 50-60 micro-inch Nickel plated.
 - 5-2:Use for 22-26 AWG stranded and solid wire
 - 6:Jack Bracket Set:ABS Black color
 - 7:PCB: FR4 UL 94V0
- Performance:**
- a.The IDC color combine two wirings of T568A & T568B.
 - b.Insertion Force: 900 grms for 8 contacts
 - c.Retention Strength: 7.7Kgs between Jack and Plug
 - d. Operation Temperature: -40°C to 70°C.
 - e.Durability:
 - e-1:Jack:750 cycles Plug-Jack mating and unmating test.
 - e-2. IDC: Max 200 punching times.

TITLE:		INCH		MM	
.X	.015		.30		
.XX	.010		.10		
.XXX	.005		.05		

DRAWN BY	MA	P/N:	UTP Cat.6 Keystone jack 180		
CHECK BY		SCALE	1:1		
APPD BY		UNIT	MM		
		SHEET	1/1		
		DATE	2021/06/25		

